

DELOTHEN® EP

Base

- solvent mixture
- free of CFC/FC-containing ingredients and aromates

Use

- preferably for cleaning equipment and dispensing units which are polluted with epoxy resin components
- cleaning has to be carried out before complete curing of the adhesive
- cleans metal, glass, ceramic, rubber, plastic
- behaviour of thermoplastic synthetics towards DELO-EP cleaner should be tested
- removes easily contaminants containing oil and grease and uncured remains of epoxy resin components
- very short evaporation time
- container should be stored closed
- evaporates without remains

Processing

- rinse equipment with equipment cleaner EP or soak contaminated parts and tools in solvent
- dry with a clean, absorbent, fluff-free towel
- repeat this process until complete cleaning
- after the cleaner and the possibly developed condensation remaining on the surfaces has completely evaporated the equipment or tool can be used again
- take measures against electrostatic charging

Technical data

Color colourless clear

evaporation time [min] approx. 2
at room temperature (approx. 23 °C)

Instructions and advice

General

The data and information provided are based on tests performed under laboratory conditions. Reliable information about the behaviour of the product under practical conditions and its suitability for a specific purpose cannot be concluded from this.

It is the user's responsibility to test the suitability of the product for the intended purpose by considering all specific requirements. Type and physical and chemical properties of the materials to be processed with the product, as well as all actual influences occurring during transport, storage, processing and use, may cause deviations in the behaviour of the product compared to its behaviour under laboratory conditions. All data provided are typical average values or uniquely determined parameters measured under laboratory conditions.

The data and information provided are therefore no guarantee for specific product properties or the suitability of the product for a specific purpose.

Occupational health and safety

see material safety data sheet

DELO Industrial Adhesives
DELO-Allee 1 · D-86949 Windach
Phone +49 8193 9900-0
Fax +49 8193 9900-144
E-Mail info@DELO.de · www.DELO.de

Specification

see quality assurance test report